

GJD 7 kVA 16 kVA Model Diesel Portable Genset



GJD Series

Diesel Portable Genset Technical Features

MODEL		GJD7000H	GJD7000H-3	GJD 7000S	GJD 7000S-3	GJD 8000H	GJD8000H-3	GJD 8000S	GJD 8000S-3	GJD 10000H	GJD 10000H-3	GJD 10000S	GJD 10000S-3	GJD 16000S	GJD 16000S-3		
GENSET	FREQUENCY	Hz.	50	50	50	50	50	50	50	50	50	50	50	50	50		
	VOLTAGE	v	220	220	220	230/400	220	230/400	220	230/400	220	230/400	220	230/400	220	230/400	
	POWER	kW	7	7	7	7	8	8	8	8	9	9	9	9	13,5	13,5	
	MAX. POWER (kW)	kW	6	6	6	6	7	7	7	7	8	8	8	8	15	15	
	AMPER	A	22,7	22,7	22,7	10,11	31,81	12,16	31,81	12,16	36,36	13,69	36,36	13,69	68A	21,6	
	PHASE		1	1	1	3	1	3	1	3	1	3	1	3	1	3	
	VOLTAGE REGULATION		AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	AVR	
	POWER FACTOR		1	1	1	0,8	1	0,8	1	0,8	1	0,8	1	0,8	1	0,8	
	NOISE (DB)	db	75	75	70	70	75	75	70	70	75	75	70	70	75	75	
	DIESEL ENGINE	ENGINE MODEL		190FAE	190FAE	190FAE	190FAE	192FAE	192FAE	192FAE	192FAE	198FAE	198FAE	198FAE	198FAE	292FAE	292FAE
BORE AND STROKE		mm	90x75	90x75	90x75	90x75	92x75	92x75	92x75	92x75	98x82	98x82	98x82	98x82	2-92x75	2-92x75	
Max.Power HP/rpm		HP/rpm	12HP/3000	12HP/3000	12HP/3000	12HP/3000	13HP/3000	13HP/3000	13HP/3000	13HP/3000	14HP/3000	14HP/3000	14HP/3000	14HP/3000	19,5/3000	19,5/3000	
STARTING SYSTEM			Electric Start														
OIL CAPACITY		Liter	1,7	1,7	1,7	1,7	1,7	1,7	1,7	1,7	1,7	1,7	1,7	1,7	4	4	
FUEL CAPACITY		Liter	15	15	16	16	15	15	16	16	22	22	30	30	45	45	
FUEL CONSUMPTION		g/kWh	280	280	280	280	242	242	242	242	230	230	230	230	330	330	
N.W/G.W(KG)		kg	115	115	190	190	125	125	200	200	135	135	210	210	320	320	
PACKAGE		DIMENSION (EXBYX) MM	mm	900x630x730	900x630x730	995x575x860	995x575x860	900x630x730	900x630x730	995x575x860	995x575x860	980x770x770	980x770x770	1100x760x860	1100x760x860	1300x700x955	1300x700x955
		20FT (SET)		76	76	72	72	76	76	72	72	54	54	30	30	24	24
	40HQ(SET)		152	152	144	144	152	152	144	144	108	108	96	96	54	54	

*Optional automatic control panels.

CERTIFICATES : TUV, CE, EUUI, GS, GSA, EPA, ETL, ISO 9001